

DaimlerChrysler AG

5

Method and computer program for controlling access  
rights to an application

10 The invention relates to a method and a computer  
program for controlling access rights of users for  
accessing, by means of a plurality of operator control  
units, at least one application which is preferably  
provided in a vehicle. Furthermore, the invention  
relates to a data carrier with such a computer program.

15

DE 198 53 665 discloses a vehicle communications system  
and method for exchanging data in a vehicle. The  
vehicle communications system comprises a central  
system controller which can grant individual and  
20 different access rights to individual applications to  
individual operator control units of the system. This  
central system controller is implemented in a central  
processing unit or some other arithmetic unit of the  
vehicle communications system. In this context the  
25 ranking, which is assigned to an operator control unit,  
can be defined either uniformly for all applications or  
individually for each application. In addition, the  
central system controller can allocate output devices  
to operator control units. The central system  
30 controller has a central priority management system.  
One aspect of this is the allocation of access rights  
for operator control units to a data bus and/or to  
individual applications. When a plurality of actions  
which have priorities attached to them coincide, the  
35 central priority management system resolves possible  
conflicts in favor of one of the actions. These  
competing actions may, for example, involve two  
operator control units with specific priorities  
requesting an application with a specific priority on

the same physical device which does not have a multi-console capability. The time ranking of the action can also be a suitable decision criterion for the solution of such a conflict.

5

The aforesaid prior art is subject to the disadvantage that in said prior art the access rights which are mentioned in it are defined essentially only for individual operator control units on a data bus and/or  
10 with respect to individual applications but the access rights are not placed in a concrete context with respect to a man/machine interface, that is to say ultimately for individual users or operator control units. When placing the access rights or access  
15 principles in a concrete context it is necessary to consider that not all applications are suitable to the same extent for all known access principles.

For this reason, taking the prior art as a basis, the  
20 object of the invention is to provide a method and a computer program for providing an access principle for applications and a data carrier with this computer program and a communications system for carrying out this method, which takes into account only the  
25 particular suitability of individual applications for specific access principles.

This object is achieved by means of the method claimed in patent claim 1. According to said claim, a method  
30 for providing an access principle for access operations of users by means of at least two operator control units to the same application which is preferably provided in a vehicle is characterized in that the access principle is provided on an application-specific  
35 basis.

Examples of access principles in the sense of the invention are in particular the "last wins" access

principle according to which that user who accesses an application last also controls this application and determines its behavior. In this context, the respective content on the two operator control units may be different. A further access principle in the sense of the invention is "in parallel in terms of switching", which provides that the same content is inevitably displayed on all operator control units, irrespective of whether different access operations are made to the same application at different operator control units. Furthermore, the "first wins" access principle, according to which that user who first accesses an application also controls this application and determines its behavior. The "first wins" access principle preferably provides for a visual and/or audible warning message to be issued by means of the second operator control unit if the application could be disrupted, or is disrupted, from the first operator control unit. Alternatively or additionally the "first wins" access principle can also be implemented in such a way that the access operation to the second operator control unit for the application is blocked until the warning message which is issued by means of the second operator control unit is acknowledged.

An application in the sense of the invention comprises at least one function which permits services to be provided for the user. Typical examples of applications are "audio", provided by an audio or hifi system, "video", provided by a video recorder, "navigation", provided by a navigation system or "communication", provided by a communications device, preferably with an Internet connection, in particular a personal computer, preferably with Internet connection. One function is respectively carried out by one of these resources units.

The advantage of the claimed, application-specific provision of access principles can be considered that this takes into account the fact that not every application is suitable for all only conceivable or available access principles. There are often technical  
5 restrictions which make an application appear suitable only for a specific access principle.

The "last wins" access principle is respectively  
10 advantageously provided for the "audio" and "video" applications, and the "parallel in terms of switching" principle is respectively advantageously provided for the navigation-system application.

15 In specific cases in the case of applications for which the "parallel in terms of switching" access principle is activated it is possible to provide a specific case of this principle, that is to say the "superuser" access principle for this application.

20 Furthermore, it is advantageous to output a visual and/or audible warning by means of an operator control unit if the sequence of an application on another operator control unit could be disrupted, or is  
25 disrupted, by the access operation from the operator control unit to the application.

The abovementioned object is also achieved by a computer program and a communications system for  
30 carrying out the claimed method, and by a data carrier with the computer program. The advantages of these solutions correspond to the advantages specified above with respect to the claimed method.

35 A single figure which shows the design of the claimed communications system in a vehicle is appended to the description.

The invention is described in more detail below in the form of exemplary embodiments and also with reference to the figure.

5 The single figure shows a vehicle 200 with wheels 230 and with a communications system 100 according to the invention. The communications system comprises a computing unit 110 for controlling applications and a plurality of operator control units 120-1...-3 for  
10 providing the applications for their users at various locations within the vehicle. The driver's seat 210-1 and the front seat passenger's seat 210-2 are jointly allocated the central operator control unit 120-1 in the cockpit of the vehicle 200, while the places on the  
15 rear bench seat 220 within the vehicle 200 are allocated the operator control units 120-2 and 120-3 at the rear of the vehicle.

The inventive allocation of individual access  
20 principles to individual applications is basically carried out automatically or is permanently predefined. It is preferably configured in such a way that it occurs basically only if a resource conflict, that is to say a conflict between users when accessing the same  
25 application from different operator control units 120, cannot be regulated, for example, by verbal agreement. A number of situation scenarios in which such a solution negotiated between people is not possible are described below:

30

- A resource which is already being used by an application called from the rear of the vehicle is requested in the cockpit of a vehicle 200, that is to say in particular from the driver's  
35 or front seat passenger's seat by means of an application. Example: the "navigation" application is being used to simultaneously access the same resource, the disk player, both

- 5 from the cockpit and from the rear of the vehicle. The passenger at the rear of the vehicle cannot release the resource because, for example, he has got out of the vehicle, has dirty fingers or does not know how he should perform the release. In this case, nevertheless it must be possible to transfer the resource from the cockpit.
- 10 - A passenger at the rear of the vehicle wishes to see a video but does not know how to set it.
- 15 - A young child is sitting at the rear of the vehicle. The young child should be prevented from alarming the driver by meddling with the audio sources, for example with a volume controller, thus bringing about a dangerous situation.
- 20 - A young person is sitting at the rear of the vehicle. The young person should be prevented from accessing expensive sources and/or sources which are not suitable for young people.
- 25 - A boss is sitting at the rear of the vehicle and does not wish a person in the cockpit, in particular the driver, to be able to read his e-mails or telephone lists.
- 30 - A passenger at the rear of the vehicle has received interesting information, for example a destination, via a specific application in the form of an information service, and would like to transfer this information to the driver as a data record.
- 35 - While the driver is using a routing function of the navigation system, the passenger at the

rear of the vehicle would like to be able to view points of interest POIs or be able to freely select details from a map using the same navigation system.

5

- The driver supports the rear seat passenger by executing working steps or functions for the rear seat passenger from the operator control unit in the cockpit in order to permit said passenger to use a specific application. To do this the driver also enters the rear seat passenger's secret code.

10

- The driver supports the rear seat passenger in a way which is analogous to the previous scenario, but this time without having to input the secret code of the rear seat passenger because the rear seat passenger does not wish to disclose this code to the driver.

15

20

Solutions for the handling of the conflict cases given above will now be presented below by way of example. These conflict cases occur primarily between the two rear operator control units. Conflicts between the operator control unit in the cockpit and the operator control units at the rear generally occur only when the navigation system and the transmission unit of the mobile telephone are accessed.

25

### 30 Entertainment

35

Entertainment comprises the "audio" and "video" applications. According to the invention, these two applications are respectively allocated the "last wins" access principle. This ensures that that user who last brought about an action, for example the changeover of a CD, controls the system. With this access principle there is no "owner" of the application in the sense

that the user alone determines who can access the application or how the application can be operated at one time. If a passenger at the rear uses one of the entertainment applications by means of a headset, a  
5 warning appears for another user who would like to access this application. If this warning is acknowledged by the passenger at the rear, the passenger at the rear thus enables access for the other user to the application. This warning is then repeated  
10 if the other, requesting user in the meantime switches over to another entertainment application, in particular another audio source.

A common resource which applications which are called  
15 from the rear of a vehicle have to share is the sound system in a single cab vehicle. Audio sources, that is to say data sources in the form of CDs etc. for the sound system are accessible only from the respective operator place in the vehicle. It is not possible to  
20 access a CD changer in the rear of the vehicle from the cockpit or to access a cassette drive at the front of the vehicle from the rear. If the sound system is currently occupied by a rear seat passenger, with the sound system accessing an audio source in the rear of  
25 the vehicle, and at the same time the driver of the vehicle attempts also to access the sound system and for this purpose activates a different source, for example at the front of the vehicle, for the sound system, a warning appears for the rear seat passenger.  
30 The rear seat passenger releases the sound system for the driver only if he acknowledges this warning. The sound system can then access the audio source which is desired by the driver and is located at the front of the vehicle, for example.

35

Communications



The "communications" application comprises in particular a mobile telephone or a communications device with Internet connection, in particular a PC with Internet connection. In these cases, the communications channel resource, in particular the connections of these applications to the outside world, is the critical parameter. It is necessary to prevent a subscriber from erroneously interrupting the connection of another subscriber. For this reason, the invention proposes that a current user of the communications channel, whether this be by means of the mobile telephone or a communications device with Internet connection, in particular by means of the PC with Internet connection, receives a warning message if another user attempts also to access this communications channel. The current user is then requested to explicitly enable his application to be interrupted by the other user by means of a confirmation, and if he does not do this the current user can continue to access the communications channel with his application and the other user is refused the permission to use the communications channel.

For the configuration of the "communications" application there are in particular three various alternatives:

1. There is only one transmission unit of a mobile telephone, specifically in the cockpit of the vehicle. In this case, the conflicts between all three operator control units, that is to say between the operator control unit in the cockpit and the two operator control units at the rear of the vehicle, are regulated.
2. There is a transmission unit of a mobile telephone in the cockpit and one at the rear of the vehicle. In this case, conflicts occur only between the two

operator control units at the rear of the vehicle since the transmission unit in the cockpit is available exclusively to the driver.

- 5     3.     There is a transmission unit in the cockpit and  
          one at the rear. The transmission unit in the  
          cockpit can according to the invention also be  
          operated from the rear. In this case, the  
10       conflicts between all three operator control units  
          are regulated.

When there is an incoming call, a warning message is also displayed on the rear operator control unit.

15   Navigation

With the "navigation" application it is not possible for reasons of resources to permit different access operations to the application in the cockpit and at the  
20   rear of the vehicle. Thus, for example, it is not possible to display different maps in the cockpit and at the rear of the vehicle or to display one map in the cockpit and at the same time enter a destination from the rear of the vehicle.

25   For this reason, according to the invention the "navigation" application is allocated the "parallel in terms of switching" access principle. This means that as long as a navigation mask is called up both on the  
30   operator control unit in the cockpit and on the operator control units at the rear, the same content is displayed on both operator control units. This occurs irrespective of whether a specific soft key or a specific hard key is pressed on one of the operator  
35   control units in the cockpit or at the rear of the vehicle. The same applies to simultaneous operator control of the "navigation" application by means of the two operator control units at the rear of the vehicle.

If the "navigation" application is activated on one of the operator control units and a MAP key, with which a map of the navigation system is called, is pressed on a different operator control unit by a different subscriber, a warning appears on the operator control unit at which the navigation system is active. The requested map will not be released on the other operator control unit until this warning is acknowledged by the original user. The same applies conversely if the map is active at the original user and a NAV key is pressed on the other operator control unit in order to call the navigations system or to transfer the navigation system into a basic mode.

In specific cases, it is possible within the scope of the "parallel in terms of switching" access principle which is to be recommended in particular for the "navigation" application to use the specific "superuser" access principle. The "superuser" access principle is distinguished by operator control which is parallel in terms of switching and which can be switched on and off by an authorized user. The latter is recommended for example if the operator control of an operator control unit 120 at the rear is to be performed from the cockpit in order to support the user of this operator control unit at the rear in his use of said unit. For this purpose there is provision that within a basic video mask on the operator control unit in the cockpit the system switches over between the left-hand or right-hand operator control unit at the rear.

The operator control is then carried out by means of the hard keys and/or soft keys of the operator control unit 120-1 in the cockpit.

During the "superuser" access principle, operator control is possible both from the cockpit and from the places at the rear of the vehicle. On the operator control units 120-2, 120-3 at the rear of the vehicle a  
5 symbol then indicates that the same image is displayed on the operator control unit 120-1 in the cockpit. This option can preferably be switched off by means of a configuration menu of the operator control unit at the rear of the vehicle. For safety reasons it is  
10 recommended that in video applications in the superuser mode only a still image is displayed on the operator control unit 120-1 in the cockpit if the vehicle's velocity exceeds a predefined threshold value.

15 Two alternative ways of exiting the superuser mode are presented:

On the one hand, pressing on an eject key and on the other hand simultaneously pressing two numerical keys.  
20 From the point of view of the man/machine interface the first alternative is preferred.

#### Child safety

25 According to the invention, access rights for children are restricted to specific applications at the places 220 in the vehicle at which children usually sit. This restriction can basically be implemented in different stages. For example, children can be refused any access  
30 rights to applications or their access rights to specific communication resources can be restricted.